



FRICON®
COOLING LIFE

HFSL line

FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Front drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-290 refrigerant gas

GENERAL DATA	HFSL 142 V
Width (mm/in)	602mm / 24in
Front (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	43kg / 95lbs
Gross capacity (gallon)	142l/37gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	1,55
Type of gas	R-134A



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Front drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-290 refrigerant gas

GENERAL DATA	HFSL 216 V
Width (mm/in)	793mm / 31in
Front (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	45g / 99lbs
Gross capacity (gallon)	216l / 57gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	2,1
Type of gas	R-134A



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Front drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-290 refrigerant gas

GENERAL DATA	HFSL 311 V
Width (mm/in)	1045mm / 41in
Front (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	54kg / 119lbs
Gross capacity (gallon)	311l / 82gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	2,7
Type of gas	R-134A



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Front drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-290 refrigerant gas



GENERAL DATA	HFSL 411 V
Width (mm/in)	1305mm / 51in
Front (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	62kg / 137lbs
Gross capacity (gallon)	411l / 108gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	2,8
Type of gas	R-134A

FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Front drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-290 refrigerant gas

GENERAL DATA	HFSL 503 V
Width (mm/in)	1545mm / 61in
Front (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	69kg / 152lbs
Gross capacity (gallon)	503l / 133gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	2,9
Type of gas	R-134A



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Front drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-290 refrigerant gas

GENERAL DATA	HFSL 550 V
Width (mm/in)	1815mm / 71in
Front (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	79kg / 174lbs
Gross capacity (gallon)	550l / 145gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	3,35
Type of gas	R-290



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-134A refrigerant gas

GENERAL DATA	HFSL 131i V
Width (mm/in)	602mm / 24in
Front height (mm/in)	705mm / 28in
Rear height (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	43kg / 95lbs
Gross capacity (gallon)	131l / 35gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	1,17
Type of gas	R-290



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-134A refrigerant gas

GENERAL DATA	HFSL 201i V
Width (mm/in)	793mm / 31in
Front height (mm/in)	705mm / 28in
Rear height (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	45kg / 99lbs
Gross capacity (gallon)	201l / 53gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	2,54
Type of gas	R-290



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-134A refrigerant gas



GENERAL DATA	HFSL 293i V
Width (mm/in)	1045mm / 41in
Front height (mm/in)	705mm / 28in
Rear height (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	54kg / 119lbs
Gross capacity (gallon)	293l / 77gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	3,73
Type of gas	R-290

FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermomether
- R-134A refrigerant gas



GENERAL DATA	HFSL 388i V
Width (mm/in)	1305mm / 51in
Front height (mm/in)	705mm / 28in
Rear height (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	62kg / 137lbs
Gross capacity (gallon)	388l / 102gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	3,35
Type of gas	R-290

FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-134A refrigerant gas



GENERAL DATA	HFSL 476i V
Width (mm/in)	1545mm / 61in
Front height (mm/in)	705mm / 28in
Rear height (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	69kg / 152lbs
Gross capacity (gallon)	476l / 126gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	3,75
Type of gas	R-290

FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Lid lock
- Backlight/Back dark
- Baskets
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- R-134A refrigerant gas

GENERAL DATA	HFSL 510i V
Width (mm/in)	1815mm / 71in
Front height (mm/in)	705mm / 28in
Rear height (mm/in)	829mm / 33in
Depth (mm/in)	679mm / 27in
Net weight (lbs)	78kg / 172lbs
Gross capacity (gallon)	510l / 135gal
Temperature range (°C)	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4
Power consumption (kWh/24h)	3,4
Type of gas	R-290



FEATURES

- Preservation of frozen products
- Static refrigeration
- Cabinet with rounded inner shapes
- Internal and external plates in pre-painted galvanized steel with high corrosion resistance
- Base frame in anodized aluminum
- Rear drain
- Slot to display price support
- High-strength double wheel casters
- Manual defrost
- Adjustable shelves
- Adjustable thermostat for low temperatures
- Low-emissivity tempered glass lid with high- efficiency sealing system
- ABS side frame, ensuring high resistance
- 80 mm thick eco-friendly polyurethane insulation
- High-impact material plastic grid with UV protection
- Without condenser micro fan, thus eliminating preventive maintenance
- Test temperature of 95°F / 75% relative air humidity
- Easy to remove lid system

OPTIONALS

- Decal Sticker
- LED lighting system
- Baskets / Tub Support
- Internal partition
- Electronic controller
- Temperature Alarm
- Analogic Thermometer
- Average double action
- R-134A refrigerant gas



GENERAL DATA	HFSL 293i V	HFSL 388i V	HFSL 476i V	HFSL 510i V
Width (mm/in)	1045mm / 41in	1305mm / 51in	1545mm / 61in	1815mm / 71in
Front height (mm/in)	705mm / 28in	705mm / 28in	705mm / 28in	705mm / 28in
Rear height (mm/in)	829mm / 33in	829mm / 33in	829mm / 33in	829mm / 33in
Depth (mm/in)	679mm / 27in	679mm / 27in	679mm / 27in	679mm / 27in
Net weight (lbs)	209kg / 461lbs	279kg / 615lbs	344kg / 758lbs	141kg / 311lbs
Gross capacity (gallon)	293l / 77gal	388l / 102gal	476l / 126gal	510l / 135gal
Temperature range (°C)	-22 ↔ -18	-22 ↔ -18	-22 ↔ -18	-22 ↔ -18
Temperature range (°F)	-7,6 ↔ -0,4	-7,6 ↔ -0,4	-7,6 ↔ -0,4	-7,6 ↔ -0,4
Power consumption (kWh/24h)	3,73	3,35	3,75	3,4
Type of gas	R-290	R-290	R-290	R-290